


STANDARD COUNTERBALANCE 10:1

標準 抗衡閥10:1

CB-H

Technical Data

技術參數



Model Code 產品型號	Cavity 閥孔型號	Capacity 流量 (l/min)	Dimension 尺寸 (mm)			Torque 安裝扭力 (Nm)	Weight 重量 (kg)	Max. Pressure 最大壓力 (bar)
			a	b	c			
CB2H	T11A	60	34.9	22.2	50	40/50	0.17	350
CB3H	T2A	120	34.9	28.6	61	60/70	0.30	350
CB6H	T17A	240	46.0	31.8	70	200/215	0.64	350
CB8H	T19A	480	63.5	41.3	90	465/500	1.47	350

Ordering Code

型號說明

CB 1 2H 2 T11A 3 L 4 K 5 N 6

- Model Code 產品型號
- Capacity (l/min) 流量
2: 60 3: 120 6: 240 8: 480
- Pilot Ratio 導壓比
H: 10:1

- Cavity 閥孔型號
T11A T2A T17A T19A

- Control 控制方式
L: standard screw adjustment 標準螺絲調整


- Functional Setting Range 設定範圍

Code 編號	J	K	C	D
Adjustment range (bar) 調壓範圍	140~350	70~175	140~350	70~175
Check (bar) 止回彈簧壓力	1.7	1.7	0.3	0.3
Standard setting (bar) 出廠設定壓力	210	140	210	140

- Seal 油封材質
N: buna-N V: viton

Turn screw clockwise to reduce setting and release load
順時針方向旋轉:降壓
逆時針方向旋轉:增壓

Full Adjustment 3 turns
全調三圈



Performance Curves

性能曲線

