


RESTRICTIVE COUNTERBALANCE 3:1

全限流 抗衡閥3:1

CB-E

Technical Data

技術參數



Model Code 產品型號	Cavity 閥孔型號	Capacity 流量 (l/min)	Dimension 尺寸 (mm)			Torque 安裝扭力 (Nm)	Weight 重量 (kg)	Max. Pressure 最大壓力 (bar)
			a	b	c			
CB2E	T11A	15	34.9	22.2	50	40/50	0.17	350
CB3E	T2A	30	34.9	28.6	61	60/70	0.30	350
CB6E	T17A	60	46.0	31.8	70	200/215	0.64	350
CB8E	T19A	80	63.5	41.3	90	465/500	1.47	350

Ordering Code

型號說明

CB 1 2E 2 T11A 3 L 4 I 5 N 6

1 Model Code 產品型號

2 Capacity (l/min) 流量
2: 15 3: 30 6: 60 8: 80

3 Pilot Ratio 導壓比
E: 3:1

4 Cavity 閥孔型號
T11A T2A T17A T19A

5 Control 控制方式
L: standard screw adjustment 標準螺絲調整


6 Functional Setting Range 設定範圍

Code 編號	H	I	A	B
Adjustment range (bar) 調壓範圍	70~280	28~105	70~280	28~105
Check (bar) 止回彈簧壓力	1.7	1.7	0.3	0.3
Standard setting (bar) 出廠設定壓力	210	70	210	70

7 Seal 油封材質
N: buna-N V: viton

Turn screw clockwise to reduce setting and release load
順時針方向旋轉:降壓
逆時針方向旋轉:增壓

Full Adjustment
3 turns
全調三圈



Performance Curves

性能曲線

